

# **SAFETY DATA SHEET**

Issue Date 24-Apr-2015 Revision Date 15-May-2015 Version 1

### 1. IDENTIFICATION

Product identifier

Product Name Henry 212 Crystal Clear Roof Patch

Other means of identification

Product Code HE212
UN/ID no. UN1133
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant.

Uses advised against No information available

### Details of the supplier of the safety data sheet

**Manufacturer Address** 

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: 800-486-1278

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

**Emergency Telephone** CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

# 2. HAZARDS IDENTIFICATION

### Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Flammable liquids	Category 3

#### Label elements

### **Emergency Overview**

### Danger

#### Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



Appearance viscous

Physical state liquid

Odor Petroleum distillates

# **Precautionary Statements - Prevention**

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wash face, hands and any exposed skin thoroughly after handling

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention

IF INHALED: Call a POISON CENTER or doctor if you feel unwell In case of fire: Use Water spray, fog or regular foam for extinction

### Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

May be harmful if swallowed Toxic to aquatic life with long lasting effects Toxic to aquatic life

Unknown acute toxicity 58% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Polymer Blend	Proprietary	30 - 60	*
Xylene	1330-20-7	10 - 30	*
Mineral Oil	8042-47-5	7 - 13	*
Ethylbenzene	100-41-4	3 - 7	*
Silica, Amorphous	112926-00-8	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

### **Description of first aid measures**

**HE212 - CRYSTAL CLEAR ROOF PATCH** 

Revision Date 15-May-2015

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash skin with soap and water.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

**Symptoms** Drowsiness.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, CO2, alcohol-resistant foam or water spray.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

No information available.

#### Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional ecological information.

# Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Advice on safe handling

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity).

Incompatible materials Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m <sup>3</sup>	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m <sup>3</sup>
		(vacated) STEL: 545 mg/m <sup>3</sup>	_
Silica, Amorphous	-	(vacated) TWA: 6 mg/m <sup>3</sup>	-
112926-00-8		TWA: 20 mppcf	
		: (80)/(% SiO2) mg/m <sup>3</sup> TWA	

### **Appropriate engineering controls**

**Engineering Controls** Showers

Eyewash stations Ventilation systems.

### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state liquid **Appearance** viscous Odor Petroleum distillates Color Odor threshold No information available clear

Remarks • Method **Property** Values

No information available Melting point / freezing point No information available

Boiling point / boiling range >= 150 °C

Flash point 24 °C

#### HE212 - CRYSTAL CLEAR ROOF PATCH

Revision Date 15-May-2015

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 9% Lower flammability limit: 1%

Vapor pressureNo information availableVapor densityNo information available

**Relative density** 0.9 - 1.3

Water solubilityNo information availableSolubility in other solventsNo information availablePartition coefficientNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information available

Kinematic viscosity >100 mm2/s

Dynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

**Other Information** 

Softening point
Molecular weight
VOC Content (%)
Density
No information available

### 10. STABILITY AND REACTIVITY

@ 40 °C

#### Reactivity

No data available

### **Chemical stability**

Stable under recommended storage conditions.

# Possibility of Hazardous Reactions

None under normal processing.

### **Conditions to avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible materials**

Strong oxidizing agents.

# **Hazardous Decomposition Products**

None known based on information supplied.

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information No data available

**Inhalation** May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Irritating to eyes.

**Skin contact** Irritating to skin.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350	= 29.08 mg/L (Rat) 4 h = 5000
1330-20-7		mg/kg (Rabbit)	ppm (Rat)4h
Mineral Oil	> 5000 mg/kg (Rat)	=	=

#### **HE212 - CRYSTAL CLEAR ROOF PATCH**

Revision Date 15-May-2015

8042-47-5			
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
100-41-4			• , ,

### Information on toxicological effects

**Symptoms** Vapors may cause drowsiness and dizziness.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. Germ cell mutagenicity No information available. Carcinogenicity No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	X

Reproductive toxicity No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. **Aspiration hazard** No information available.

# Numerical measures of toxicity - Product Information

ATEmix (oral) 3,770.00 ATEmix (dermal) 1,689.00 ATEmix (inhalation-gas) 919.00 ATEmix (inhalation-dust/mist) 1.97 ATEmix (inhalation-vapor) 99,999.00

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

68 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene	-	13.4: 96 h Pimephales promelas	3.82: 48 h water flea mg/L EC50
1330-20-7		mg/L LC50 flow-through 2.661 -	0.6: 48 h Gammarus lacustris mg/L
		4.093: 96 h Oncorhynchus mykiss	LC50
		mg/L LC50 static 13.5 - 17.3: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		13.1 - 16.5: 96 h Lepomis	
		macrochirus mg/L LC50	
		flow-through 19: 96 h Lepomis	
		macrochirus mg/L LC50 7.711 -	
		9.591: 96 h Lepomis macrochirus	
		mg/L LC50 static 23.53 - 29.97: 96 h	
		Pimephales promelas mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 780: 96 h	
		Cyprinus carpio mg/L LC50 30.26 -	
		40.75: 96 h Poecilia reticulata mg/L	
		LC50 static	
Ethylbenzene	4.6: 72 h Pseudokirchneriella		1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 438: 96 h	mykiss mg/L LC50 static 4.2: 96 h	EC50
	Pseudokirchneriella subcapitata	Oncorhynchus mykiss mg/L LC50	
	mg/L EC50 2.6 - 11.3: 72 h	semi-static 7.55 - 11: 96 h	
	Pseudokirchneriella subcapitata	Pimephales promelas mg/L LC50	
	mg/L EC50 static 1.7 - 7.6: 96 h	flow-through 32: 96 h Lepomis	
	Pseudokirchneriella subcapitata	macrochirus mg/L LC50 static 9.1 -	
	mg/L EC50 static	15.6: 96 h Pimephales promelas	
		mg/L LC50 static 9.6: 96 h Poecilia	
		reticulata mg/L LC50 static	

#### Persistence and degradability

Not readily biodegradable.

#### Bioaccumulation

Chemical Name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
Mineral Oil 8042-47-5	>6
Ethylbenzene 100-41-4	3.118

Other adverse effects No information available

Ozone Not applicable

# 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene	-	Included in waste stream:	-	U239
1330-20-7		F039		
Ethylbenzene	-	Included in waste stream:	=	-
100-41-4		F039		

Chemical Name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Ethylbenzene	Toxic
100-41-4	Ignitable

# 14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1133
Proper shipping name Adhesives

Hazard Class 3
Packing Group III

**Description** May be shipped as a limited quantity if inner packages do not exceed 5L each. Consult

regulations for additional information.

**TDG** 

UN/ID no. UN1133
Proper shipping name Adhesives

Hazard Class 3
Packing Group III

**Description** May be shipped as a limited quantity if inner packages do not exceed 5L each. Consult

regulations for additional information.

<u>IATA</u>

UN/ID no. UN1133
Proper shipping name Adhesives

Hazard Class 3
Packing Group III

**IMDG** 

UN/ID no. UN1133
Proper shipping name Adhesives

Hazard Class 3
Packing Group III

**Description** May be transported as a limited quantity in inner packages not exceeding 5L. Consult

regulations for additional limitations

### 15. REGULATORY INFORMATION

All components used in this product are on the TSCA Inventory and the Canadian DSL.

# International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies

**ENCS** Does not comply

IECSCCompliesKECLCompliesPICCSCompliesAICSComplies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

### SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardNoFire hazardNoSudden release of pressure hazardNoReactive HazardNo

### **CWA (Clean Water Act)**

This product contains substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb	-	-	X

1330-20-7				
Ethylbenzene	1000 lb	X	X	X
100-41-4				

### **CERCLA**

This material, as supplied, contains substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

### **US State Regulations**

#### **California Proposition 65**

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

### **U.S. State Right-to-Know Regulations**

#### U.S. EPA Label Information

**EPA Pesticide Registration Number** Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and Chemical

Properties -

Health hazards 2 Flammability 2 Physical hazards 0 Personal protection X

 Issue Date
 24-Apr-2015

 Revision Date
 15-May-2015

Revision Note

No information available

#### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**